

MATERIAL SAFETY DATA SHEET

BARE KNUCKLES Ultra
Stripper

MSDS Ref. No: 4021
Date Prepared: 1/19/2005
Date Revised: 1/19/2005

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME/USE: BARE KNUCKLES Ultra Stripper

Distributor

Myers Supply, Inc.
831 Third St.
Hot Springs, AR 71913

Telephone Number: 501-623-7742
Emergency Telephone (24 hours): 888-627-8740

2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>INGREDIENT(S)</u>	<u>CAS#</u>	<u>% BY WEIGHT</u>
2-Butoxyethanol	111-76-2	10 - 25
Ethanolamine	141-43-5	10 - 25
Sodium hydroxide	1310-73-2	1 - 1.5
Sodium xylene sulfonate	1300-72-7	1 - 1.5

See Section 8 for Exposure Limits NA - Not Applicable

OSHA REGULATORY STATUS: This product is classified as hazardous under OSHA regulations.

WHMIS CLASS: Class E; Class D- Division 2B

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Clear, Red Liquid . Fragrant Ammonia Odor. Causes Eye and Skin Burns. Harmful if Swallowed. May be Harmful if Inhaled.

POTENTIAL HEALTH EFFECTS (See Section 11 for Toxicological Information)

PRIMARY ROUTE(S) OF EXPOSURE: Eye Skin Contact Skin Absorption
 Inhalation Ingestion

EFFECTS OF ACUTE EXPOSURE

EYES: Causes eye burns. Symptoms may include pain, tearing, redness, and eye injury.

SKIN: Causes skin burns. Symptoms may include pain, redness, swelling, scarring, and skin damage. May be absorbed through the skin and may cause effects as described under Inhalation (see below).

INHALATION: May be harmful if inhaled. High concentrations of vapor or mist may cause nose, throat and respiratory tract irritation. Symptoms may include coughing, wheezing, shortness of breath and a disagreeable metallic taste. High concentrations of vapor or mist may also cause central nervous system effects including headache, dizziness and nausea.

INGESTION: Harmful if swallowed. May cause mouth, throat and stomach burns. Symptoms may include nausea, vomiting, diarrhea, and severe stomach pain. May also cause central nervous system effects including headache, dizziness and

BARE KNUCKLES Ultra Stripper

weakness.

EFFECTS OF CHRONIC EXPOSURE: Prolonged inhalation of high concentrations of concentrated alkaline materials above exposure limits (See Section 8, Exposure Controls/Personal Protection) can cause respiratory tract injury.

MEDICAL CONDITIONS AGGRAVATED: May aggravate pre-existing eye, skin and respiratory conditions.

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water while holding eyelids apart. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not put any medication in the victim's eyes unless instructed by a physician. Get immediate medical attention.

SKIN: Immediately flush with plenty of water for at least 15 minutes, then wash with soap and water. Immediately remove contaminated clothing. Get medical attention if irritation develops or persists. Thoroughly wash (or discard) clothing before reuse. Destroy contaminated shoes.

INHALATION: Remove to fresh air. If not breathing, give respiration; if breathing is difficult, give oxygen (by trained personnel only). Get immediate medical attention.

INGESTION: Do not induce vomiting. Rinse mouth out with water. Drink large quantities of water. Get immediate medical attention. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD: > 93°C (200°F)TCC

FLAMMABLE LIMITS: Not applicable.

AUTOIGNITION TEMPERATURE: Not applicable.

EXTINGUISHING MEDIA: Use extinguishing media appropriate for surrounding fire.

HAZARDOUS COMBUSTION PRODUCTS: Normal products of combustion (carbon monoxide and carbon dioxide) and nitrogen oxides.

FIRE AND EXPLOSION HAZARDS: None known.

FIRE FIGHTING INSTRUCTIONS: This product is not flammable. As in any fire, MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear should be worn.

6. ACCIDENTAL RELEASE MEASURES

See Section 8, Exposure Controls/Personal Protection and Section 3, Hazard Identification. Floors may be slippery. Use care to avoid falling. Ventilate spill area. Contain and isolate spill. Keep non-essential personnel from entering spill area. Use mop and absorbent to collect material for proper disposal. Use non-metallic implements for cleaning and collection. Rinse area with water.

7. HANDLING AND STORAGE

HANDLING: Follow label use directions. Do not mix with other chemicals unless instructed by label directions. Avoid contact with skin, eyes and clothing. Use with adequate ventilation. Avoid breathing vapor or mist. Wash thoroughly after handling. Immediately remove contaminated clothing. Wash clothing and equipment before reuse. Destroy contaminated shoes. Empty containers retain residue and may be hazardous (See Section 14, Transport Information).

STORAGE: Keep container closed when not in use. Store away from incompatible materials. (See Section 10, Stability and Reactivity).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE: Where eye contact is possible, wear chemical splash goggles (ANSI Z87.1-approved).

SKIN: Where skin contact is possible, chemical-resistant gloves should be worn. When additional skin contact is possible, other

BARE KNUCKLES Ultra Stripper

protective equipment and clothing (e.g., footwear) may be needed. All contaminated clothing should be removed immediately and cleaned (or discarded) before reuse.

RESPIRATORY: No respiratory protection is required if general room ventilation is adequate and airborne concentrations are kept below exposure limits. When exposure limits are exceeded, use appropriate respiratory protection (NIOSH/MSHA) to prevent overexposure.

ENGINEERING CONTROLS: Good general room ventilation is expected to be adequate. Local exhaust ventilation (e.g., fans) may be necessary when general ventilation does not keep airborne concentrations below exposure limits.

EXPOSURE LIMITS:

INGREDIENT(S)

2-Butoxyethanol

Ethanolamine

Sodium hydroxide

Sodium xylene sulfonate

NA - Not Available

OSHA PEL/STEL

25 ppm 120 mg/m³ /
Skin

3 ppm 8 mg/m³ /
6 ppm 15 mg/m³

2 mg/m³ /
Ceiling

NA

ACGIH TLV/STEL

25 ppm 121 mg/m³ /
Skin

3 ppm 7.5 mg/m³ /
6 ppm 15 mg/m³

2 mg/m³ /
Ceiling

NA

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Fragrant Ammonia

APPEARANCE: Clear, Red

pH: 13.0 to 14.0

PERCENT VOLATILE BY WEIGHT: 97

VAPOR PRESSURE: Not Available

VAPOR DENSITY: Not Available

BOILING POINT: Not Available

FREEZING/MELTING POINT: Not Available

SOLUBILITY IN WATER: Complete

EVAPORATION RATE: Not Available

SPECIFIC GRAVITY: 1.02

VISCOSITY: Water Thin

OCTANOL/WATER PARTITION COEFFICIENT: Not Available

ODOR THRESHOLD: Not Available

10. STABILITY AND REACTIVITY

STABILITY (CONDITIONS TO AVOID): Stable.

POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: None known.

INCOMPATIBLE MATERIALS: Oxidizers (e.g., bleach), strong acids (e.g., hydrochloric acid), reactive metals (e.g., aluminum), and nitrosating agents (e.g., sodium nitrite).

11. TOXICOLOGICAL INFORMATION

ACUTE DATA: This product causes eye and skin burns. Based on acute toxicity testing, this product is harmful if swallowed. Acute overexposure to high concentrations of 2-butoxyethanol by skin absorption, ingestion and inhalation has caused blood, liver, and kidney effects in laboratory animals. The following data are available for this product and its ingredients:

BARE KNUCKLES Ultra Stripper

<u>PRODUCT/INGREDIENT</u>	<u>ORAL LD₅₀ (rat)</u>	<u>DERMAL LD₅₀ (rabbit)</u>	<u>INHALATION LC₅₀ (rat)</u>
BARE KNUCKLES Ultra Stripper	<2000 mg/kg	>2000 mg/kg	Not Available
2-Butoxyethanol	470 - mg/kg	220 - mg/kg	450 - ppm (4-hr)
Ethanolamine	1720 - mg/kg	1018 - mg/kg	Not Available
Sodium hydroxide	Not Available	1350 - mg/kg	Not Available
Sodium xylene sulfonate	650 - 4000 mg/kg	3000 - mg/kg	Not Available

SENSITIZATION DATA: No data available.

CHRONIC DATA:

Repeated inhalation of high concentrations of alkaline materials has been reported to cause impairment of lung function with shortness of breath, chemical pneumonia and pulmonary edema. Prolonged overexposure to high concentrations of 2-butoxyethanol by skin absorption, ingestion and inhalation has caused blood, liver and kidney effects in laboratory animals. Prolonged overexposure to high concentrations of ethanolamine by inhalation and ingestion has caused liver and kidney effects in laboratory animals.

REPRODUCTIVE/TERATOGENIC DATA: No data available.

CARCINOGENIC/MUTAGENIC DATA: Not listed as carcinogenic by NTP, IARC, or ACGIH or regulated as a carcinogen by OSHA.

SYNERGISTIC MATERIALS: No data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Disposal of this material should be in accordance with local, state or provincial and federal regulations. The unused product, as manufactured, is a RCRA hazardous waste (Corrosive-D002) in accordance with 40 CFR 261. The product has not been evaluated by the Toxicity Characteristic Leachate Procedure (TCLP). According to RCRA, it is the responsibility of the waste generator to ensure proper disposal.

14. TRANSPORT INFORMATION

DOT/TDG HAZARDOUS MATERIAL DESCRIPTION: Corrosive Liquid, N.O.S.

DOT/TDG TECHNICAL NAME: Ethanolamine, sodium hydroxide

DOT/TDG HAZARD CLASS: 8

UN ID No./P.I.N. No.: 1760

DOT/TDG PACKING GROUP: II

NAERG: 154

15. REGULATORY INFORMATION

Not meant to be all-inclusive---selected regulations represented.

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Under 40 CFR 370.2, this product meets the following hazard categories: Immediate, Delayed.

313 REPORTABLE INGREDIENTS: 2-Butoxyethanol is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 under the chemical category Glycol Ethers.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: Not reportable under CERCLA.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product complies with all TSCA inventory requirements.

MASSACHUSETTS, NEW JERSEY, PENNSYLVANIA RIGHT-TO-KNOW:

BARE KNUCKLES Ultra Stripper

INGREDIENT(S)

Water
2-Butoxyethanol
Ethanolamine
Sodium hydroxide
Sodium xylene sulfonate

NA - Not Applicable

CAS NO. STATE LISTING

7732-18-5 Not Listed
111-76-2 MA, NJ, PA
141-43-5 MA, NJ, PA
1310-73-2 MA, NJ, PA
1300-72-7 Not Listed

CANADA


WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): Class E- Corrosive material; Class D- Division 2B, chronic toxic effects. This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

HMIS RATING

HEALTH	*	3
FLAMMABILITY		0
REACTIVITY		0
PERSONAL PROTECTION		-

NFPA CODES:



APPROVED BY: EH&S/Regulatory Affairs

MSDS STATUS

Revision No: 3

Revision #: 3

This MSDS replaces the November 02, 2001 MSDS. Any changes in information are as follows:

In Section 14

DOT Technical Name

APPROVAL DATE: 04/01/2002

The information on this data sheet represents our current data and best opinion as to the proper use in handling of the product under normal foreseeable conditions. Any use of this product which is not in conformance with this data sheet or product label, or which involves using the product in combination with any other product or any other process is the responsibility of the user.
1/19/2005 AB