

EMERGENCY MEDICAL Telephone# 1-888-627-8740 (24 Hrs)
PRODUCT HAZARD RATINGS (HMIS): Health = 1, Fire = 2, Reactivity = 0, Protective Equipment = B
(Rating Legend: 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

SECTION I

SNYERS SUPPLY, INC. TELEPHONE NUMBER FOR INFORMATION: 501-623-7742
P831 THIRD STREET DATE PRINTED: 8/18/03
HOT SPRINGS AR 71913 NAME OF PREPARER: Ron Cepa EDITED BY: Billy Johnson

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Chemical Names (LD50-Oral Rat)	SEC 313	Exposure Limits TLV/TWA	SARA Title III PEL	ACGIH	OSHA	% By Wt.
-----------------------------------	---------	----------------------------	-----------------------	-------	------	----------

D-Limonene		5g/kg	-	NA	NA	1-5.0
Liquefied Petroleum Gas (CAS# 68476-85-7)		NA	-	NA	1000ppm	1000ppm 1-10.0

Unidentified ingredients are not considered hazardous under the Federal Hazard Communication Standard.

Components Listed As A Suspected Carcinogen: None

SECTION III - PHYSICAL CHARACTERISTICS

Boiling Point: NA Vapor Pressure (psig): 126@130F Specific Gravity (H2O=1): <1
Solubility/Water: Almost complete Vapor Density (AIR=1): >1 Evaporation Rate (Ether=1): <1
Appearance and Odor: coarse white mist, citrus aroma

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: This product is considered to be non flammable as described in 16CFR 1500.45.
Flammable Limits - % Volume In Air (Propellant): LEL: 1.8 UEL: 9.2
Extinguishing Media: Carbon dioxide, foam and/or dry chemical may be used.
Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.
Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.
Unusual Fire and Explosion Hazards: At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

SECTION V - REACTIVITY DATA

Stability: Stable Hazardous Polymerization: NA
Incompatibility (Materials to Avoid): Strong oxidizing agents
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide and additional toxic chemicals may be formed in small amounts.
Conditions to Avoid: Do not store above 54C-130F. Keep away from heat, direct sunlight, open flames or sparks. Dropping of containers may cause bursting.

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry - Inhalation: X Eyes: X Skin: X Ingestion: X
Signs and Symptoms of Exposure: Inhalation may cause dizziness, drowsiness and throat irritation. Eye contact may be irritating. Skin contact may cause slight redness.
Medical Conditions Generally Aggravated by Exposure: Preexisting skin or eye disorders and upper respiratory inflammation may be aggravated by exposure to this product.

Emergency and First Aid Procedures: Eye Contact: Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get medical attention if irritation persists. Skin Contact: Remove contaminated clothing. Flush skin with water, follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. Inhalation: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention. Ingestion: Get medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Releases or Spilled: Remove all sources of ignition and ventilate area. Soak up spill with an inert absorbent and place into a designated disposal container. Consult local regulatory agency for proper disposition of material.
Waste Disposal Method: Do not puncture or incinerate containers. When contents are depleted continue to depress button until all gas is expelled. Dispose of container in accordance with local, state, and federal regulations.
Handling And Storing: Avoid breathing vapor. Keep away from heat and flame. Use with adequate ventilation. Do not puncture or incinerate containers. Do not expose to direct sunlight or store at temperatures above 130F (54C). Store as Level I Aerosol (NFPA 30B).
Other Precautions: Please read and follow the directions on the product label; they are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

SECTION VIII - EMPLOYEE PROTECTION

Respiratory Protection (Type): None required if good ventilation is maintained. If exposure exceeds occupational exposure limits (Sec. II), use a NIOSH approved respirator to prevent overexposure.
Ventilation: Local exhaust is adequate under normal conditions, mechanical ventilation is optional.

