

***** MATERIAL SAFETY DATA SHEET *****
ROCK BOTTOM CONCRETE SEAL

MYERS SUPPLY, INC. 831 THIRD STREET HOT SPRINGS, AR 71913 (501) 623-7742

EMERGENCY ASSISTANCE

For emergency assistance involving chemicals call (888) 627-8740

PRODUCT NAME: ROCK BOTTOM CONCRETE SEALER DATE PREPARED: 06-14-04
IDENTITY: CLEAR W.B. CONCRETE SEALER DATE REVISED:
CHEMICAL FAMILY: STYRENE/ACRYLIC EMULSION REVISION NO:

HAZARDOUS INGREDIENTS

MATERIAL	CAS #	OSHA PEL	AGCIH TLV	SARA III LIST
Propylene Glycol Phenyl Ether	770-35-4	N/E	N/E	No

HAZARD RATINGS:

Health: 1 Special: none
Fire: 0
Reactivity: 0

HAZARD RATING SCALE:

0=Minimal 3=Serious
1=Slight 4=Severe
2=Moderate

This product contains no reported carcinogens or suspected carcinogens.

PHYSICAL DATA

BOILING POINT, @ 760 mm Hg: > 212F SOLUBILITY IN WATER: Complete
SPECIFIC GRAVITY @ 77 F: 1.032 VAPOR PRESSURE, mm Hg: N/D
VAPOR DENSITY, (AIR=1): N/D VOLATILES, BY VOLUME: >75 %
APPEARANCE @ 77 F: Milky White ODOR: Mild
pH (100 %) 8.0-9.0 EVAPORATION RATE (B/A=1): N/D

FIRE AND EXPLOSION HAZARD DATA

FLASH POINT, TCC: 201F. FLAMMABLE LIMITS IN AIR, % BY VOLUME: LOWER: 2.0 UPPER: N/D. EXTINGUISHING MEDIA: None Required. SPECIAL FIRE FIGHTING PROCEDURES: None known. Unusual Fire & Explosion Hazards: None known.

HEALTH HAZARD DATA

EFFECTS OF EXCESSIVE OVEREXPOSURE. PRIMARY ROUTES OF ENTRY ARE: Eye Contact: Direct contact with product may cause mild irritation. Skin Contact: Prolonged or repeated contact may cause mild irritation. Inhalation: Prolonged overexposure to vapors and spray mist in poorly ventilated areas may cause nose and throat irritation. Ingestion: May cause mouth, throat, esophagus and stomach irritation, nausea, vomiting and diarrhea.

EMERGENCY AND FIRST AID PROCEDURES

Eye Contact: Flush with water for 15 minutes. If irritation persists, get medical attention. Skin Contact: Remove contaminated clothing. Wash with soap and water. If irritation persists, get medical attention. Inhalation: Remove to fresh air. Ingestion: DO NOT INDUCE VOMITING. Drink 3 to 4

***** MATERIAL SAFETY DATA SHEET *****
ROCK BOTTOM CONCRETE SEAL

glasses of water. Call a physician immediately. Never give anything by mouth to an unconscious person.

REACTIVITY HAZARD DATA

Stability: Stable. Hazardous Polymerization: None. Incompatibility: None known. Conditions to Avoid: High temperatures. Hazardous Decomposition Products: Incomplete combustion can produce carbon monoxide.

CONTROL AND PROTECTIVE MEASURES

Respiratory Protection: Avoid breathing of spray mist. If sprayed wear mechanical filter respirator to remove solid particles of over spray. Follow respirator manufacturer's directions for respirator use. Ventilation: Provide general clean air dilution or local exhaust ventilation in volume and pattern to prevent air contaminant concentration build-up. Refer to OSHA Standard 1910.94. Protective Gloves: As required to minimize prolonged or repeated skin contact. Eye Protection: Avoid contact with eyes. Use safety eyewear with side shields. Other Protective Clothing & Equipment: None normally required. Eye bath and safety shower.

PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Of Spill Or Leak: Contain spill. Keep out of surface waters & sewers or water courses entering or leading to surface waters. Absorb spill with inert material, then place in a chemical waste container. For large spills, dike for later disposal. Dispose of according to local, state, and federal regulations. Precautions To Be Taken In Handling & Storage: Do not store above 100 deg. F. Keep container closed when not in use. Shelf life 2 years. Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Read & follow label directions. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full. DO NOT TAKE INTERNALLY.

FOR ADDITIONAL INFORMATION

CONTACT: Technical Director, Sunbelt Laboratories, during business hours, central time; (281) 261-4747.
