

# MATERIAL SAFETY DATA SHEET

## SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<b>PRODUCT NAME</b>	U.W.CLEAR COAT WAX		
<b>PRODUCT CODE</b>	UW-CC-5G	<b>DISTRIBUTOR</b>	Myers Supply, Inc.
<b>ISSUE DATE</b>	02/23/05	<b>STREET ADDRESS</b>	831 Third St.
<b>SUPERCEDES</b>	05/03/01	<b>CITY, STATE ZIP</b>	Hot Springs, AR 71913
		<b>PHONE</b>	(501) 623-7742

### EMERGENCY TELEPHONE NUMBER

1-888-627-8740

## SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

### EXPOSURE LIMITS

HAZARDOUS INGREDIENTS	CAS No.	OSHA PEL/TLV	ACGIH TLV	STEL	OTHER LIMITS
Mineral Seal Oil	64741-44-2	NA	NA	NA	NA
Butoxyethanol	111-76-2	25 ppm	25 ppm	NA	NA
Quaternary Ammonium Compounds	61789-77-3	NE	NE	NE	NA
Isopropanol	67-63-0	400 ppm	400 ppm	500 ppm	NA

## SECTION 3 – HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** Causes eye and skin irritation.Harmful if swallowed.Harmful if inhalation exposure limits are exceeded.

### POTENTIAL HEALTH EFFECTS

**INGESTION** ..... Irritation, headache, nausea, CNS depression.

**INHALATION** ..... Irritation to mucous membranes, pneumonitits, pulmonary edema.

**EYE CONTACT** ..... Irritation.

**SKIN CONTACT** ..... Irritation.

## SECTION 4 – FIRST AID MEASURES

**INGESTION** Drink large quantities of water or milk. DO NOT INDUCE VOMITING. **See a physician immediately.**

**INHALATION** If mists are formed, leave area until mists have dissipated. If irritation occurs, see a physician.

**EYE CONTACT** Flush with water for 15 minutes, occasionally lifting eyelids. See a physician if irritation persists.

**SKIN CONTACT** Remove contaminated clothing. Wash skin with soap and water. Wash clothing before reuse. See a physician if irritation persists.

**NOTE TO PHYSICIAN** Treatment based on judgment of the physician in response to reactions of the patient.

## SECTION 5 – FIRE FIGHTING MEASURES

FLASH POINT / METHOD	>212° F/COC	FLAMMABLE LIMITS	NA
% VOLATILE	NA		
EXTINGUISHING MEDIA		Dry chemical, water mist, alcohol foam, CO2.	
SPECIAL FIRE FIGHTING PROCEDURES		Firefighters should wear a self-contained breathing apparatus as in all chemical fires.	
FIRE AND EXPLOSION HAZARDS		Can form combustible mixtures with air when heated.	

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

RESPONSE TO SPILLS	Stop leak. Dike flow of spilled material. Absorb spill on inert material (i.e. saw dust, chalk dust). Flush residual to sewer.
--------------------	--

## SECTION 7 – HANDLING AND STORAGE

HANDLING PRECAUTIONS	Wash hands before eating. Keep container tightly closed when not in use.
STORAGE PRECAUTIONS	Store in a dry, cool place away from strong oxidizers.

## SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTIONS

HYGIENIC PRACTICES	Normal procedures for good hygiene. Observe label precautions. Use personal protection equipment.
ENGINEERING CONTROLS	Use general mechanical ventilation to remove vapors at the source. Eyewash station is recommended.
X RESPIRATOR	Not required.
X GOGGLES / FACE SHIELD	Required; chemical splash goggles.
APRON	Not necessary.
X GLOVES	Required; chemical resistant type.
BOOTS	Not necessary.

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Orange liquid.	BOILING POINT	>>212° F
ODOR	Cherry	VAPOR PRESSURE	NA
pH	8.5	VAPOR DENSITY	NA
SPECIFIC GRAVITY	0.890	EVAPORATION RATE (butyl acetate=1)	< 1
SOLUBILITY IN WATER	Complete		

## SECTION 10 – STABILITY AND REACTIVITY

CHEMICAL STABILITY	<b>STABLE</b>	X	<b>UNSTABLE</b>
<b>CONDITIONS TO AVOID</b>	No special precautions beyond standard safe industrial practices.		
INCOMPATIBILITY	Strong oxidizers.		
HAZARDOUS PRODUCTS OF DECOMPOSITION	Oxides of carbon and nitrogen.		
POLYMERIZATION	<b>WILL NOT OCCUR</b>	X	<b>MAY OCCUR</b>
<b>CONDITIONS TO AVOID</b>	None.		

## SECTION 11 – TOXICOLOGICAL INFORMATION

### CARCINOGENICITY

X THIS PRODUCT CONTAINS A KNOWN OR SUSPECTED CARCINOGEN  
THIS PRODUCT DOES NOT CONTAIN ANY KNOWN OR ANTICIPATED CARCINOGENS ACCORDING TO THE CRITERIA OF THE NTP ANNUAL REPORT ON CARCINOGENS AND OSHA 29 CFR 1910,Z

### OTHER EFFECTS

**ACUTE** Central nervous system depression, headache, nausea, dizziness and coughing.  
**CHRONIC** Chronic exposure to Butoxyethanol may cause damage to liver, kidney and blood forming organs.  
**ORAL LD/50** Unknown.

## SECTION 12 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL Dispose of solids by incineration or recycling according to Federal, State, and local authorities.

## SECTION 13 – TRANSPORT INFORMATION

DOT CLASSIFICATION	<b>HAZARDOUS</b>	<b>NOT HAZARDOUS</b>	X
DESCRIPTION	NA		
HM CODE	000		

## SECTION 14 – OTHER INFORMATION

### HMIS CLASSIFICATION

1	<b>BLUE</b>	HEALTH HAZARD
1	<b>RED</b>	FLAMMABILITY
0	<b>YELLOW</b>	REACTIVITY
None	<b>WHITE</b>	SPECIAL HAZARD

Information contained in this MSDS refers only to the specific material designated and does not relate to any process or use involving other materials. This information is based on data believed to be reliable, and the Product is intended to be used in a manner that is customary and reasonably foreseeable. Since actual use and handling are beyond our control, no warranty, express or implied, is made and no liability is assumed by Myers Supply, Inc. in connection with the use of this information.